

Professional Tripod & Carry Case

The SVP professional tripod is very sturdy and suitable for the deployment of microwave links and outside broadcast equipment.

On its fabrication aluminium has been used to achieve a solid stable operating platform while being light enough to carry, install and use it easily.

The clamping system used is cine clamp60. The tripod head has full 360 degree rotation in azimuth and +/- 50 degree in elevation. The tripod has a position lock in azimuth and elevation. A tensioned coil spring assists balance control with heavy loads using the operator arm.

Fully adjustable legs enable optimum height adjustment with a central lock and supports struts to provide extra stability.

For tripod protection during transportation there is available the CC-TP carry case.



Characteristics

TP - TRIPOD:

Height

Max: 1.500 mm

Min: 820 mm

Load capacity

70 kg

Foot Span

1.600 mm

Packed size

1.000 x 240 x 210 mm

Weight

10 kg

Support arm

400mm

Head adjustment

Azimuth 360°

Elevation +/- 50°

Fine adjust

Elevation +/- 2,5°

CC-TP - CARRY CASE FOR THE TRIPOD:

Material:

Outside: TTX1 High strength resin

Inside: Neopreno, foam

Type of closure

Double hinged locking system

Size:

Outside: 113 x 28,5 x 33,5 cm(WxHxD)

Inside: 108,5 x 27,0 x 24,3 cm(WxHxD)

Weight:

6,3 kg

Temperature range:

-40° to +80°



Design and specifications are subject to changes without prior notice. 05/15